

FIBER & ACCESS / OUTDOOR DROP CABLE

Dielectric FTTH Drop Cable

CX-DROP-2X3

A compact outdoor drop cable for field-cut FTTH service installations and configured connector assemblies.

**Flexible installation lengths**

Field-cut cable supports routing to the length required at each installation.

Fully dielectric construction

Dual parallel FRP strength members support the flat cable profile.

Outdoor jacket

UV-stabilized black HDPE jacket for outdoor access-network use.

PRODUCT SPECIFICATIONS

Specification	Details
Fiber	1 × ITU-T G.657.A2 single-mode
Nominal cable dimensions	2.0 × 3.0 mm
Tight buffer diameter	0.9 mm
Strength members	Dual parallel FRP
Jacket	UV-stabilized black HDPE
Attenuation at 1310 nm	≤0.34 dB/km
Attenuation at 1550 nm	≤0.20 dB/km
Bend radius: installation / static	≥20 × cable diameter / ≥10 × cable diameter
Operating / storage temperature	−40 to +70 °C / −50 to +80 °C
Standard reel length	2,000 m
Standard reference	YD/T 1951-2018

TERMINATION OPTIONS

Supports configured hardened-connector assemblies and field-installed SC/APC connectors. CPX-LX11-B supports the specified 2.0 × 3.0 mm cable profile; match the end connection to the network interface.

Practical product support. Personal service.

sales@componexx.com | componexx.com

CX-DROP-2X3